

# Camera Link Cable

## KEY FEATURES

- ❖ Connector 1: 26 pos, MDR, molded hood, with thumbscrews, color black
- ❖ Connector 2: 26 pos, MDR, molded hood, with thumbscrews, color black
- ❖ Wire: (28AWGx1PR+A)x11 + 26AWGx2C+2EMAB 90%, UL20276, color black
- ❖ Fully support Camera Link standard for Base, Medium, Full
- ❖ PoCL compliant
- ❖ Length: 0.5, 1, 2, 3, 5, 7,10 meter, +/- 25mm
- ❖ Flammability: AWM VW-1

## Applications

- ❖ Machine vision cameras and grabbers
- ❖ Semiconductor wafer inspection
- ❖ High speed printing inspection
- ❖ Automated product inspection (e.g. food, drinking or pharmaceutical products)
- ❖ High resolution and real-time analysis for science, sports, automobile tests, and 3-D animation.
- ❖ High precision security surveillance (e.g. border control, airport)
- ❖ Traffic surveillance/control and vehicle license plate reading/recording (e.g. toll booth)
- ❖ Cameras placed in harsh environment (e.g. nuclear plant, steel mill or undersea monitoring)



## MDR26/MDR26 cable assembly

**FD-618-14T26-xx-0LC**

Connector 1



Connector 2




Fresh Digit  
[www.freshdigit.com](http://www.freshdigit.com)  
[info@freshdigit.com](mailto:info@freshdigit.com)


Tel: 1-949-204-0288

FD-618-14T26-xx-0LC

# CABLE ASSEMBLY DRAWING



# PIN ASSIGNMENT



**Note:**  
 Each pair is shielded and has continuity to the drain wires (Pin 13, 14) and overall foil shield. Overall braid shield is connected to connector shells and is isolated from other shields

# ORDERING INFORMATION

| Part #              | Description  |
|---------------------|--|
| FD-618-14T26-xx-0LC | Camera Link cable assembly, MDR26 plug to MDR26 plug, PoCL compliant |
|                     | xx = meter, (0.5, 01, 02, 03, 05, 07, 10)                            |

**Fresh Digit**  
[www.freshdigit.com](http://www.freshdigit.com)  
[info@freshdigit.com](mailto:info@freshdigit.com)

Tel: 1-949-204-0288 Fax: 1-949-296-0931